



SERIES R301

Two-Piece Ball Valve



INTRODUCTION

TAWD Two-Piece Ball Valve provides quick and easy flow control for liquids and gases, making them ideal for any application requiring a simple on/off operation.

Technical summary

SERIES R301-10

- ATEX
- Blow-out Proof Stem Design



SIZE RANGE	Full port	1/4" ~ 3"
PRESSURE RATING	Full port	1000 PSI / CLASS 400 / PN 63
END CONNECTIONS	Threaded	
SEAT MATERIAL	PTFE, RTFE, CTFE, TFM1600, MG1241, STFE	
BODY MATERIAL (ASTM)	CF8M, CF3M, CF8, CF3, WCB, Titanium Alloy (Gr. C-2)	
BODY MATERIAL (EN)	1.4408, 1.4409, 1.4308, 1.4309, 1.0619	
HANDLE OPTIONS	Oval Handle, Economical Stem Extension	

STANDARD OF COMPLIANCE

MATERIAL CERTIFICATION	EN 10204-3.1
DESIGN	ASME B16.34
THREADED END CONNECTIONS	NPT ASME B1.20.1 BSPP ISO 228-1 BSPT ISO 7-1 DIN 2999
PRESSURE TESTING	API 598
MARKING	ISO 5209
CE APPROVAL	2014 / 68 / EU Module H
QUALITY ASSURANCE	ISO 9001:2015

INTRODUCTION

TAWD Two-Piece Ball Valve provides quick and easy flow control for liquids and gases, making them ideal for any application requiring a simple on/off operation.

Technical summary

SERIES R301-20

- ATEX
- Blow-out Proof Stem Design
- Drilled and Tapped Mounting Pad



SIZE RANGE	Full port	1/4" ~ 4"
PRESSURE RATING	Full port	1000 PSI / CLASS 400 / PN 63
END CONNECTIONS	Threaded	
SEAT MATERIAL	PTFE, RTFE, CTFE, TFM1600, MG1241, STFE	
BODY MATERIAL (ASTM)	CF8M, CF3M, CF8, CF3, WCB, Titanium Alloy (Gr. C-2)	
BODY MATERIAL (EN)	1.4408, 1.4409, 1.4308, 1.4309, 1.0619	
HANDLE OPTIONS	Oval Handle, Economical Stem Extension	

STANDARD OF COMPLIANCE

MATERIAL CERTIFICATION	EN 10204-3.1
DESIGN	ASME B16.34
THREADED END CONNECTIONS	NPT ASME B1.20.1 BSPP ISO 228-1 BSPT ISO 7-1 DIN 2999
PRESSURE TESTING	API 598
MARKING	ISO 5209
CE APPROVAL	2014 / 68 / EU Module H
QUALITY ASSURANCE	ISO 9001:2015

INTRODUCTION

TAWD Two-Piece Ball Valve provides quick and easy flow control for liquids and gases, making them ideal for any application requiring a simple on/off operation.

Technical summary

SERIES R301-30

- ATEX
- Blow-out Proof Stem Design
- Drilled and Tapped Mounting Pad




SIZE RANGE	Reduced port	1/4" ~ 2"	
PRESSURE RATING	Reduced port	1/4" ~ 1"	2000 PSI / CLASS 800 / PN 125
		1-1/4" ~ 2"	1500 PSI / CLASS 600 / PN 100
END CONNECTIONS	Threaded		
SEAT MATERIAL	PTFE, RTFE, CTFE, TFM1600, MG1241, STFE		
BODY MATERIAL (ASTM)	CF8M, CF3M, CF8, CF3, WCB, Titanium Alloy (Gr. C-2)		
BODY MATERIAL (EN)	1.4408, 1.4409, 1.4308, 1.4309, 1.0619		
HANDLE OPTIONS	Oval Handle, Economical Stem Extension		

STANDARD OF COMPLIANCE

MATERIAL CERTIFICATION	EN 10204-3.1
DESIGN	ASME B16.34
THREADED END CONNECTIONS	NPT ASME B1.20.1 BSPP ISO 228-1 BSPT ISO 7-1 DIN 2999
PRESSURE TESTING	API 598
MARKING	ISO 5209
CE APPROVAL	2014 / 68 / EU Module H
QUALITY ASSURANCE	ISO 9001:2015

CONSTRUCTION - BILL OF MATERIAL

SERIES R301-10 1/4"~ 3" Full port



NO.	Parts	Material	Qty
1	Body	CF8M	1
2	End Cap	CF8M	1
3	Ball	SS316	1
4	Seat	PTFE / RTFE	2
5	Joint Gasket	PTFE	1
6	Thrust Washer	PTFE	1
7	Stem	SS316	1
8	Gland Packing	PTFE	1 Set
9	Gland Bush	SS304	1
10	Stem Washer	SS304	1
11	Stem Nut	SS304	1
12	Handle	SS304	1
13	Handle Cover	VINYL	1
14	Locking Device	SS304	1

*Optional : Anti-static stem with ATEX certification







DIMENSIONS(mm)

SIZE	ØA	C	D	E	F	G
1/4"	11.5	55	50	100	1/4" PF - NPT - PT	13
3/8"	11.5	55	50	100	3/8" PF - NPT - PT	13
1/2"	15	65	60	130	1/2" PF - NPT - PT	16
3/4"	20	72	64	130	3/4" PF - NPT - PT	17
1"	25	84	71	165	1" PF - NPT - PT	19
1-1/4"	32	94	78	165	1-1/4" PF - NPT - PT	22
1-1/2"	38	110	86	190	1-1/2" PF - NPT - PT	22.5
2"	50	126	95	190	2" PF - NPT - PT	26
3"	80	178	148	250	3" PF - NPT - PT	12

CONSTRUCTION - BILL OF MATERIAL

SERIES R301-20 1/4"~ 4" Full port



NO.	Parts	Material	Qty
1	Body	CF8M	1
2	End Cap	CF8M	1
3	Ball	SS316	1
4	Seat	PTFE / RTFE	2
5	Joint Gasket	PTFE	1
6	Thrust Washer	PTFE	1
7	Stem	SS316	1
8	Gland Packing	PTFE	1 Set
9	Gland Bush	SS304	1
10	Stem Washer	SS304	1
11	Stem Nut	SS304	1
12	Handle	SS304	1
13	Handle Cover	VINYL	1
14	Locking Device	SS304	1
15	Handle Washer	SS304	@


*Optional : Anti-static stem with ATEX certification
@ 4" (1pcs)

DIMENSIONS(mm)

SIZE	øA	øB	C	D	E	F1	F	J	G	H	H1	H2	W1	W2	W3	W4
1/4"	11.5	8	55	50	100	13	1/4" PF - NPT - PT	10-24UNC	5	8	9.8	22.3	12.7	28.5	-	-
3/8"	12.5	8	55	50	100	13	3/8" PF - NPT - PT	10-24UNC	5	8	9.8	22.3	12.7	28.5	-	-
1/2"	15	9.5	65	60	130	16	1/2" PF - NPT - PT	10-24UNC	6.5	10.5	11	25.6	12.7	28.5	-	-
3/4"	20	9.5	74.6	64	130	17	3/4" PF - NPT - PT	10-24UNC	6.5	10.5	11	25.6	22.4	35	-	-
1"	25	11	88	71	165	19	1" PF - NPT - PT	10-24UNC	8	11.5	13.5	31.5	23.4	35	-	-
1-1/4"	32	11	102	78	165	22	1-1/4" PF - NPT - PT	1/4-20UNC	8	11.5	13.5	31.5	25.4	38.1	-	-
1-1/2"	38	14	110	86	190	22.5	1-1/2" PF - NPT - PT	1/4-20UNC	9.7	12	15.6	35.1	25.4	38.1	-	-
2"	50	14	125	95	190	26	2" PF - NPT - PT	1/4-20UNC	9.7	9.5	15.6	30.6	25.4	38.1	-	-
2-1/2"	65	19	160.6	130	250	31	2-1/2" PF - NPT - PT	1/4-20UNC	12	17	24.5	54.2	-	-	59	61
3"	80	19	178	148	250	34	3" PF - NPT - PT	1/4-20UNC	12	18	24.5	55.2	-	-	70	71
4"	100	19	240	175	250	43	4" PF - NPT - PT	1/4-20UNC	15	20.8	24.5	57.4	-	-	100	78.5

CONSTRUCTION - BILL OF MATERIAL

SERIES R301-30 1/4"~ 2" Reduced port



NO.	Parts	Material	Qty
1	Body	CF8M	1
2	End Cap	CF8M	1
3	Ball	SS316	1
4	Seat	PTFE / RTFE	2
5	Joint Gasket	PTFE	1
6	Thrust Washer	PTFE	1
7	Stem	SS316	1
8	Gland Packing	PTFE	1 Set
9	Gland Bush	SS304	1
10	Stem Washer	SS304	1
11	Stem Nut	SS304	1
12	Handle	SS304	1
13	Handle Cover	VINYL	1
14	Locking Device	SS304	1

*Optional : Anti-static stem with ATEX certification



DIMENSIONS(mm)

SIZE	øA	øB	C	D	E	F1	F	J	G	H	H1	H2	W1	W2
1/4"	9.5	8	51	50	100	11	1/4" PF - NPT - PT	10-24UNC	5	6	8	17.7	12.7	28.5
3/8"	9.5	8	51	50	100	11	3/8" PF - NPT - PT	10-24UNC	5	6	8	17.7	12.7	28.5
1/2"	12.5	8	59.5	50	100	15	1/2" PF - NPT - PT	10-24UNC	5	8	9.8	22.6	12.7	28.5
3/4"	15	9.5	70	53	130	16.5	3/4" PF - NPT - PT	10-24UNC	6.5	10.5	11	25	22.4	35
1"	20	9.5	84	64	130	19.5	1" PF - NPT - PT	10-24UNC	6.5	9	11	25	22.4	35
1-1/4"	25	11	91	66	165	20	1-1/4" PF - NPT - PT	10-24UNC	8	13	13.5	33	22.4	35
1-1/2"	32	11	104	79	165	22	1-1/2" PF - NPT - PT	1/4-20UNC	8	11.5	13.5	31	25.4	38.1
2"	38	14	117	83	190	23	2" PF - NPT - PT	1/4-20UNC	9.7	9	15.6	31.6	25.4	38.1

TECHNICAL DATA | Breakaway torque / Cv and Kv values / Weight


R301-10					
Valve size	Torque		Cv values	Kv values (M³/h)	Weight (Kg)
	N.m	lbs.in			
1/4"	5	44	7	6	0.3
3/8"	5	44	8	7	0.3
1/2"	7	62	15	13	0.5
3/4"	8	71	40	34	0.6
1"	14	124	70	60	1.0
1-1/4"	18	160	110	94	1.3
1-1/2"	26	230	250	213	1.9
2"	34	301	430	366	3
3"	78	691	1100	935	9.9

R301-20					
Valve size	Torque		Cv values	Kv values (M³/h)	Weight (Kg)
	N.m	lbs.in			
1/4"	5	44	7	6	0.3
3/8"	5	44	8	7	0.3
1/2"	7	62	15	13	0.5
3/4"	8	71	40	34	0.6
1"	14	124	70	60	1.0
1-1/4"	18	160	110	94	1.5
1-1/2"	26	230	250	213	2.0
2"	34	301	430	366	3.0
2-1/2"	56	496	700	595	6.8
3"	78	691	1100	935	9.9
4"	124	1099	2000	1700	20.6


R301-30					
Valve size	Torque		Cv values	Kv values (M³/h)	Weight (Kg)
	N.m	lbs.in			
1/4"	5	44	7	6	0.3
3/8"	5	44	7	6	0.3
1/2"	7	62	8	7	0.4
3/4"	8	71	15	13	0.5
1"	14	124	40	34	0.8
1-1/4"	18	160	70	60	1.1
1-1/2"	26	230	110	94	1.6
2"	34	301	250	213	2.4

TECHNICAL DATA | Pressure - Temperature diagram

R301-10 / R301-20
Seat material : PTFE / RTFE



R301-30
Seat material : PTFE / RTFE





Transworld Steel Enterprise Co., Ltd.

Tel +886 4 2271 6107 **Fax** +886 4 2271 6127

Address No. 34, Gongye 14th Rd., Dali Dist.,
Taichung City, 412038, Taiwan (R.O.C.)



Established in 1992
TAWD has dedicated over 30 years to
manufacturing premium ball valves

INNOVATION

INTEGRITY

STRICT SELECTION

➡ DISTRIBUTOR NORWAY | ✉ post@jsc.no | 🏠 www.jsc.no